

Colonna1	KZ	OK	OK-N	OK-J	MINI
<b>MODELLO:</b> MODEL:	BLACK ROCK 2	LK2	LK2 NEWS	LKJ2	R16
<b>OMOLOGA:</b> HOMOLOGATION:	033-EZ-11	033-ES-20	033-EN-20	033-EJ-30	033-EM-01
<b>DESCRIZIONE:</b> DESCRIPTION:	2 stroke single cylinder	2 stroke single cylinder	2 stroke single cylinder	2 stroke single cylinder	2 stroke single cylinder
<b>GRUPPO:</b> GROUP:	2	2	2	2	3
<b>ALESAGGIO:</b> BORE:	Ø 54 mm	Ø 53,90 mm	Ø 53,90 mm	Ø 53,90 mm	Ø 41,80 mm
<b>ALESAGGIO MASSIMO:</b> MAX BORE:	Ø 54,09 mm	Ø 54,10 mm	Ø 54,10 mm	Ø 54,10 mm	Ø 42,10 mm
<b>CORSA:</b> STROKE:	54.4 mm	54,37 mm	54,37 mm	54,37 mm	43 mm
<b>CILINDRATA:</b> DISPLACEMENT:	125 cc	125 cc	125 cc	125 cc	60 cc
<b>TRAVASI:</b> PORTS:	5/3	5/3	5/3	5/3	2
<b>ALIMENTAZIONE:</b> INLET SYSTEM:	VALVOLA A LAMELLE REED-VALVE	VALVOLA A LAMELLE REED-VALVE	VALVOLA A LAMELLE REED-VALVE	VALVOLA A LAMELLE REED-VALVE	PISTON PORTED
<b>LUBRIFICAZIONE:</b> LUBRIFICATION:	A MISCELA OIL MIXTURE	A MISCELA OIL MIXTURE	A MISCELA OIL MIXTURE	A MISCELA OIL MIXTURE	A MISCELA OIL MIXTURE
<b>ACCENSIONE:</b> IGNITION SYSTEM:	PVL	SELETTRA	SELETTRA	SELETTRA	SELETTRA
<b>TRASMISSIONE:</b> TRANSMISSION:	CAMBIO A 6 RAPPORTI 6 SPEED GEARBOX	MONOMARCIA DIRECT DRIVE	MONOMARCIA DIRECT DRIVE	MONOMARCIA DIRECT DRIVE	MONOMARCIA DIRECT DRIVE
<b>RAFFREDDAMENTO:</b> COOLING SYSTEM:	A LIQUIDO LIQUID COOLING	A LIQUIDO LIQUID COOLING	A LIQUIDO LIQUID COOLING	A LIQUIDO LIQUID COOLING	AD ARIA AIR COOLING
<b>AVVIAMENTO:</b> STARTER	A SPINTA PUSH START	A SPINTA PUSH START	A SPINTA PUSH START	A SPINTA PUSH START	ELETTRICO ELECTRIC START
<b>FRIZIONE:</b> CLUTCH:	A DISCHI MULTIPLI MULTI-DISC CLUTCH	NO	NO	NO	CENTRIFUGA A SECCO CENTRIFUGAL DRY CLUTCH
<b>CARBURATORE:</b> CARBURETOR:	VALVOLA GAS PIANA FLAT THROTTLE VALVE	VALVOLA A FARFALLA BUTTERFLY THROTTLE	VALVOLA A FARFALLA BUTTERFLY THROTTLE	VALVOLA A FARFALLA BUTTERFLY THROTTLE	VALVOLA GAS CILINDRICA PISTON-TYPE THROTTLE VALVE
<b>MASSIMO NUM DI GIRI:</b> MAX RPM LIMIT:	16.000	16.000	15.000	14.000	14.000